


Panel Schematic



01/22/19 BOM				
TAG	DESCRIPTION	QTY	CATALOG	MFG
HMI109	7" TOUCH SCREEN	1	6015936	REDLION
G109	POWER SUPPLY, 24VDC, 8A	1	6021099	MEAN WELL
	COMPACT SPLICING TERMINAL	2	6019512	WAGO
	ENCLOSURE, 7" SCREEN	1	6021618	OKW
CBL109	RJ45 8 POSITION 6" PIGTAIL	1	6021619	CALRAD

System Information

- 24 Fans Max
- 4 Groups Max
- Timer Controls *Standard*
- Temperature Control *Optional*
- Humidity Control *Optional*
- BMS Integration *BACnet TCP/IP*
- Requires 120V Power Supply
- NEMA 4X Indoor Rated
- Password Lockout Capable
- Field Configurable

All Communication Cable by Others

General Notes

The information contained herein is property and confidential to 4Front Engineered Solutions, and is to be used solely for the express purpose of consideration and development of the article described herein and may not be reproduced or disseminated without the permission of 4Front Engineered Solutions. 4Front Engineered Solutions reserves the right to incorporate product improvements without prior notice.

NOTES:

1) BUILDING STRUCTURE MUST BE SUFFICIENT TO SUPPORT THE FAN INSTALLATION. CONSULT A REGISTERED ARCHITECT OR PROFESSIONAL ENGINEER.

2) ELECTRICAL CONTRACTOR SHALL ENSURE THAT ALL ELECTRICAL WORK MEETS LOCAL ELECTRICAL CODES.

3) GENERAL CONTRACTOR SHALL ENSURE EQUIPMENT INSTALLATION MEETS ALL APPLICABLE BUILDING CODES.

4) STANDARD MOUNT ACCOMMODATES I-BEAM INSTALLATION. FOR GLULAM/WOOD BEAM, Z-PURLIN OR TRUSS BRIDGES PLEASE NOTE ON ORDER.

5) THE VFD ENCLOSURE MUST BE INSTALLED OUTSIDE AND A SAFE DISTANCE FROM THE BLADE DIAMETER FOR SERVICE PURPOSES.

6) MULTI-FAN INSTALLATION INCLUDES ONE TOUCHSCREEN HMI KIT.

7) NOTE:
THE INSTALLATION OF HVLS FANS IN BUILDINGS EQUIPPED WITH SPRINKLERS, INCLUDING "ESFR" SPRINKLERS, SHALL COMPLY WITH THE FOLLOWING:

(A) THE HVLS FAN SHALL BE CENTERED APPROXIMATELY BETWEEN FOUR ADJACENT SPRINKLERS.

(B) THE VERTICAL CLEARANCE FROM THE HVLS FAN TO THE SPRINKLER DEFLECTOR SHALL BE A MINIMUM OF 3 FT (0.9M).

(C) ALL HVLS FANS SHALL BE INTERLOCKED TO SHUT DOWN IMMEDIATELY UPON RECEIVING A WATERFLOW SIGNAL FROM THE ALARM SYSTEM IN ACCORDANCE WITH THE REQUIREMENTS OF NFPA 72.

Firm Name and Address


ENTRE//MATIC

1612 Hutton Drive, Suite 140
Carrollton, TX 75006

Drawn By:	Regional Sale Manager:
CRE	TBD
Date:	Drawing Number:
04/06/2020	6021616S
Scale:	Sheet Number: Rev:
NTS	1 OF 10 C

Revision	Date	Drawn By	Description	Revision	Date	Reference	Description
A	01/22/2019	CRE	INITIAL DRAWING				
B	06/06/2019	CRE	ADDED BACNET CONNECTION				
C	04/06/2020	CRE	Updated BACNET address tables				

Commercial Fan Layout



General Notes

The information contained herein is property and confidential to 4Front Engineered Solutions, and is to be used solely for the express purpose of consideration and development of the article described herein and may not be reproduced or disseminated without the permission of 4Front Engineered Solutions. 4Front Engineered Solutions reserves the right to incorporate product improvements without prior notice.

NOTES:

- 1) BUILDING STRUCTURE MUST BE SUFFICIENT TO SUPPORT THE FAN INSTALLATION. CONSULT A REGISTERED ARCHITECT OR PROFESSIONAL ENGINEER.
- 2) ELECTRICAL CONTRACTOR SHALL ENSURE THAT ALL ELECTRICAL WORK MEETS LOCAL ELECTRICAL CODES.
- 3) ELECTRICAL DISCONNECT AND FUSING PROVIDED BY OTHERS.
- 4) GENERAL CONTRACTOR SHALL ENSURE EQUIPMENT INSTALLATION MEETS ALL APPLICABLE BUILDING CODES.
- 5) STANDARD MOUNT ACCOMMODATES I-BEAM INSTALLATION. FOR GLULAM /WOOD BEAM, Z-PURLIN OR TRUSS BRIDGES PLEASE NOTE ON ORDER.
- 6) THE VFD ENCLOSURE MUST BE INSTALLED OUTSIDE AND A SAFE DISTANCE FROM THE BLADE DIAMETER FOR SERVICE PURPOSES.
- 7) MULTI-FAN INSTALLATION INCLUDES ONE TOUCHSCREEN HMI KIT.
- 8) ALL CONDUIT BY OTHERS
- 9) NOTE:
THE INSTALLATION OF HVLS FANS IN BUILDINGS EQUIPPED WITH SPRINKLERS, INCLUDING "ESFR" SPRINKLERS, SHALL COMPLY WITH THE FOLLOWING:
(A) THE HVLS FAN SHALL BE CENTERED APPROXIMATELY BETWEEN FOUR ADJACENT SPRINKLERS.
(B) THE VERTICAL CLEARANCE FROM THE HVLS FAN TO THE SPRINKLER DEFLECTOR SHALL BE A MINIMUM OF 3 FT (0.9M).
(C) ALL HVLS FANS SHALL BE INTERLOCKED TO SHUT DOWN IMMEDIATELY UPON RECEIVING A WATERFLOW SIGNAL FROM THE ALARM SYSTEM IN ACCORDANCE WITH THE REQUIREMENTS OF NFPA 72.

REVIEW DRAWING

THIS DRAWING IS NOT INTENDED FOR CONSTRUCTION.
PLEASE CONSULT WITH REGISTERED ARCHITECT OR PROFFESIONAL ENGINEER FOR ALL LOADS ANALYSIS AND SPECIFICATIONS CONFORMITY.

Firm Name and Address

by


ENTREMATIC

1612 Hutton Drive, Suite 140
Carrollton, TX 75006

Revision	Date	Drawn By	Description	Revision	Date	Reference	Description
A	01/22/2019	CRE	INITIAL DRAWING				
B	06/06/2019	CRE	ADDED BACNET CONNECTION				
C	04/06/2020	CRE	Updated BACNET address tables				

Drawn By:	CRE	Regional Sale Manager:	TBD
Date:	04/06/2020	Drawing Number:	6021616S
Scale:	NTS	Sheet Number:	4 OF 10
		Rev:	C

Commercial Fan Field Wiring



General Notes

The information contained herein is property and confidential to 4Front Engineered Solutions, and is to be used solely for the express purpose of consideration and development of the article described herein and may not be reproduced or disseminated without the permission of 4Front Engineered Solutions. 4Front Engineered Solutions reserves the right to incorporate product improvements without prior notice.

NOTES:

1) BUILDING STRUCTURE MUST BE SUFFICIENT TO SUPPORT THE FAN INSTALLATION. CONSULT A REGISTERED ARCHITECT OR PROFESSIONAL ENGINEER.

2) ELECTRICAL CONTRACTOR SHALL ENSURE THAT ALL ELECTRICAL WORK MEETS LOCAL ELECTRICAL CODES.

3) ELECTRICAL DISCONNECT AND FUSING PROVIDED BY OTHERS.

4) GENERAL CONTRACTOR SHALL ENSURE EQUIPMENT INSTALLATION MEETS ALL APPLICABLE BUILDING CODES.

5) STANDARD MOUNT
ACCOMMODATES I-BEAM
INSTALLATION. FOR GLULAM /WOOD
BEAM, Z-PURLIN OR TRUSS BRIDGES
PLEASE NOTE ON ORDER.

6) THE VFD ENCLOSURE MUST BE INSTALLED OUTSIDE AND A SAFE DISTANCE FROM THE BLADE DIAMETER FOR SERVICE PURPOSES.

7) MULTIFAN INSTALLATION INCLUDES ONE TOUCHSCREEN HMI KIT.

8) ALL CONDUIT BY OTHERS

9) NOTE:
THE INSTALLATION OF HVLS FANS IN
BUILDINGS EQUIPPED WITH
SPRINKLERS, INCLUDING "ESFR"
SPRINKLERS, SHALL COMPLY WITH
THE FOLLOWING:

(A) THE HVLS FAN SHALL BE CENTERED APPROXIMATELY BETWEEN FOUR ADJACENT SPRINKLERS.
(B) THE VERTICAL CLEARANCE FROM THE HVLS FAN TO THE SPRINKLER DEFLECTOR SHALL BE A MINIMUM OF 3 FT (0.9M).
(C) ALL HVLS FANS SHALL BE INTERLOCKED TO SHUT DOWN IMMEDIATELY UPON RECEIVING A WATERFLOW SIGNAL FROM THE ALARM SYSTEM IN ACCORDANCE WITH THE REQUIREMENTS OF NFPA 72.

REVIEW DRAWING
THIS DRAWING IS NOT INTENDED FOR
CONSTRUCTION.
PLEASE CONSULT WITH REGISTERED ARCHITECT
OR PROFESSIONAL
ENGINEER FOR ALL LOADS ANALYSIS
AND SPECIFICATIONS CONFORMITY.

Firm Name and Address

by

ENTRE//MATIC

1612 Hutton Drive, Suite 140
Carrollton, TX 75006

Drawn By:

Regional Sale Manager:

Date: 04/06/20


Drawing Number:
6021616S

Scale:

Sheet Number:

Rev:

Commercial Fan Optional Hardware Field Wiring



General Notes

The information contained herein is property and confidential to 4Front Engineered Solutions, and is to be used solely for the express purpose of consideration and development of the article described herein and may not be reproduced or disseminated without the permission of 4Front Engineered Solutions. 4Front Engineered Solutions reserves the right to incorporate product improvements without prior notice.

NOTES:

- 1) ELECTRICAL CONTRACTOR SHALL ENSURE THAT ALL ELECTRICAL WORK MEETS LOCAL ELECTRICAL CODES.
- 2) RECOMMENDED COMMUNICATION CABLE BELDEN 8723
- 3) ALL CONDUIT BY OTHERS

REVIEW DRAWING

THIS DRAWING IS NOT INTENDED FOR CONSTRUCTION.
PLEASE CONSULT WITH REGISTERED ARCHITECT OR PROFESSIONAL ENGINEER FOR ALL LOADS ANALYSIS AND SPECIFICATIONS CONFORMITY.

Firm Name and Address

by

ENTREMATIc

1612 Hutton Drive, Suite 140
Carrollton, TX 75006

Revision	Date	Drawn By	Description	Revision	Date	Reference	Description
A	01/22/2019	CRE	INITIAL DRAWING				
B	06/06/2019	CRE	ADDED BACNET CONNECTION				
C	04/06/2020	CRE	Updated BACNET address tables				

Drawn By:	CRE	Regional Sale Manager:	TBD
Date:	04/06/2020	Drawing Number:	6021616S
Scale:	NTS	Sheet Number:	7 OF 10
		Rev:	C

Fan	BACnet Address	Register Description	Expected Data	Result/Status	Notes
Temp1	AO1001	Forward Start SP	> 0	Temperature SP to Start in Forward	Scaled by 10, so write 800 to get a value of 80
	AO1002	Reverse Start SP	> 0	Temperature SP to Start in Reverse	Scaled by 10, so write 300 to get a value of 30
	AO1003	Forward increment SP	> 0	Temperature FWD Inc	Scaled by 10, so write 300 to get a value of 30
	AO1004	Reverse increment SP	> 0	Temperature REV Inc	Scaled by 10, so write 300 to get a value of 30
	AI1001	Scaled Temperature	##	Temperature FB	
	AI1011	Temperature/Humidity Sensor LOC	0 1	Good communication No communication	0 = False 1 = True
Temp2	AO1005	Forward Start SP	> 0	Temperature SP to Start in Forward	Scaled by 10, so write 800 to get a value of 80
	AO1006	Reverse Start SP	> 0	Temperature SP to Start in Reverse	Scaled by 10, so write 300 to get a value of 30
	AO1007	Forward increment SP	> 0	Temperature FWD Inc	Scaled by 10, so write 300 to get a value of 30
	AO1008	Reverse increment SP	> 0	Temperature REV Inc	Scaled by 10, so write 300 to get a value of 30
	AI1002	Scaled Temperature	##	Temperature FB	
	AI1012	Temperature/Humidity Sensor LOC	0 1	Good communication No communication	0 = False 1 = True
Temp3	AO1009	Forward Start SP	> 0	Temperature SP to Start in Forward	Scaled by 10, so write 800 to get a value of 80
	AO1010	Reverse Start SP	> 0	Temperature SP to Start in Reverse	Scaled by 10, so write 300 to get a value of 30
	AO1011	Forward increment SP	> 0	Temperature FWD Inc	Scaled by 10, so write 300 to get a value of 30
	AO1012	Reverse increment SP	> 0	Temperature REV Inc	Scaled by 10, so write 300 to get a value of 30
	AI1003	Scaled Temperature	##	Temperature FB	
	AI1013	Temperature/Humidity Sensor LOC	0 1	Good communication No communication	0 = False 1 = True
Temp4	AO1013	Forward Start SP	> 0	Temperature SP to Start in Forward	Scaled by 10, so write 800 to get a value of 80
	AO1014	Reverse Start SP	> 0	Temperature SP to Start in Reverse	Scaled by 10, so write 300 to get a value of 30
	AO1015	Forward increment SP	> 0	Temperature FWD Inc	Scaled by 10, so write 300 to get a value of 30
	AO1016	Reverse increment SP	> 0	Temperature REV Inc	Scaled by 10, so write 300 to get a value of 30
	AI1004	Scaled Temperature	##	Temperature FB	
	AI1014	Temperature/Humidity Sensor LOC	0 1	Good communication No communication	0 = False 1 = True
	AO1017	Forward Start SP	> 0	Humidity SP to Start in Forward	Scaled by 10, so write 800 to get a value of 80
	AO1018	Reverse Start SP	> 0	Humidity SP to Start in Reverse	Scaled by 10, so write 300 to get a value of 30
	AO1019	Forward increment SP	> 0	Humidity FWD Inc	Scaled by 10, so write 300 to get a value of 30
	AO1020	Reverse increment SP	> 0	Humidity REV Inc	Scaled by 10, so write 300 to get a value of 30
Humid1	AI1005	Humidity	##	Humidity FB	
	AO1021	Forward Start SP	> 0	Humidity SP to Start in Forward	Scaled by 10, so write 800 to get a value of 80
	AO1022	Reverse Start SP	> 0	Humidity SP to Start in Reverse	Scaled by 10, so write 300 to get a value of 30
	AO1023	Forward increment SP	> 0	Humidity FWD Inc	Scaled by 10, so write 300 to get a value of 30
	AO1024	Reverse increment SP	> 0	Humidity REV Inc	Scaled by 10, so write 300 to get a value of 30
	AI1006	Humidity	##	Humidity FB	
Humid2	AO1025	Forward Start SP	> 0	Humidity SP to Start in Forward	Scaled by 10, so write 800 to get a value of 80
	AO1026	Reverse Start SP	> 0	Humidity SP to Start in Reverse	Scaled by 10, so write 300 to get a value of 30
	AO1027	Forward increment SP	> 0	Humidity FWD Inc	Scaled by 10, so write 300 to get a value of 30
	AO1028	Reverse increment SP	> 0	Humidity REV Inc	Scaled by 10, so write 300 to get a value of 30
Humid3	AI1007	Humidity	##	Humidity FB	
	AO1029	Forward Start SP	> 0	Humidity SP to Start in Forward	Scaled by 10, so write 800 to get a value of 80
	AO1030	Reverse Start SP	> 0	Humidity SP to Start in Reverse	Scaled by 10, so write 300 to get a value of 30
	AO1031	Forward increment SP	> 0	Humidity FWD Inc	Scaled by 10, so write 300 to get a value of 30
Humid4	AO1032	Reverse increment SP	> 0	Humidity REV Inc	Scaled by 10, so write 300 to get a value of 30
	AI1008	Humidity	##	Humidity FB	
	AO1033	Wind Set Point	5-15	Set Point to shut off fans	5-15 MPH
	AO1034	Time	1-20	Seconds before shut off	Time above set point before shutoff
Wind	AO1035	Restart Time	>60	Seconds before restart	Time below set point before restart
	AI1009	Scaled Wind Speed	##	Wind Speed	Displayed in the selected units
	AI1010	Direction	##	Wind Direction	
	AI1015	Wind Sensor LOC	0 1	Good communication No communication	0 = False 1 = True
	Fire Control Panel	AI1016	Fire Alarm Contact	0	Fire Alarm Activated
1				No Fire Alarm	1 = True
AI1017		Fire Alarm Panel LOC	0	Good communication	0 = False
			1	No communication	1 = True

DATA	DECIMAL VALUE	PANEL INDICATION	DESCRIPTION
H10	16	E.OC1	OVERCURRENT TRIP DURING ACCELERATION
H11	17	E.OC2	OVERCURRENT TRIP DURING CONSTANT SPEED
H12	18	E.OC3	OVERCURRENT TRIP DURING DECELERATION OR STOP
H20	32	E.OV1	REGENERATIVE OVERVOLTAGE TRIP DURING ACCELERATION
H21	33	E.OV2	REGENERATIVE OVERVOLTAGE TRIP DURING CONSTANT SPEED
H22	34	E.OV3	REGENERATIVE OVERVOLTAGE TRIP DURING DECELERATION OR STOP
H30	48	E.THT	INVERTER OVERLOAD TRIP (ELECTRONIC THERMAL RELAY FUNCTION)
H31	49	E.THM	MOTOR OVERLOAD TRIP (ELECTRONIC THERMAL RELAY FUNCTION)
H40	64	E.FIN	FIN OVERHEAT
H52	82	E.ILF	INPUT PHASE LOSS
H60	96	E.OLT	STALL PREVENTION

DATA	DESCRIPTION
0	NO ALARM/FAN OK
1	SHORT CIRCUIT
2	CURRENT LIMIT
3	CURRENT LIMIT TRIP
4	UNDER VOLTAGE TRIP
6	OVER VOLTAGE TRIP
8	STOP MODE
9	FLASH ERROR
13	WATCHDOG ERROR
22	COMMUNICATION WATCHDOG ERROR

General Notes

The information contained herein is property and confidential to 4Front Engineered Solutions, and is to be used solely for the express purpose of consideration and development of the article described herein and may not be reproduced or disseminated without the permission of 4Front Engineered Solutions. 4Front Engineered Solutions reserves the right to incorporate product improvements without prior notice.

NOTES:

1) ELECTRICAL CONTRACTOR SHALL ENSURE THAT ALL ELECTRICAL WORK MEETS LOCAL ELECTRICAL CODES.

2) RECOMENDED COMMUNICATION CABLE BELDEN 8723

3) ALL CONDUIT BY OTHERS

REVIEW DRAWING

THIS DRAWING IS NOT INTENDED FOR CONSTRUCTION.

PLEASE CONSULT WITH REGISTERED ARCHITECT OR PROFFESIONAL ENGINEER FOR ALL LOADS ANALYSIS AND SPECIFICATIONS CONFORMITY.

Firm Name and Address

by

ENTREMATIC

1612 Hutton Drive, Suite 140
Carrollton, TX 75006

Revision	Date	Drawn By	Description	Revision	Date	Reference	Description	Drawn By:	Regional Sale Manager:
A	01/22/2019	CRE	INITIAL DRAWING					CRE	TBD
B	06/06/2019	CRE	ADDED BACNET CONNECTION					Date: 04/06/2020	Drawing Number: 6021616S
C	04/06/2020	CRE	Updated BACNET address tables					Scale: NTS	Sheet Number: 10 OF 10 Rev: C