



The Summit HVLS Fan features an epic design with enormous size, performance and savings. Producing a 2-3 mph breeze equivalent to a 4-7 degree reduction in perceived temperature, the Summit works hard to ensure your facility reaches its full productivity potential.

The Summit HVLS fan is designed to move extraordinary amounts of air, helping your entire facility run smoothly, while providing substantial energy savings. Not only will you feel the difference of a noticeably cooler space, but you'll also reduce stagnant air, alleviate hot and cold spots and keep food dry and fresh. The Summit is available in diameters ranging from 8 feet to 24 feet to accommodate your space and a variety of customization options.

KEY FEATURES

- Extruded aluminum black anodized blades
- 8-24 feet (2.4-7.3 M) in diameter
- · Rotary airfoil winglet design
- Trouble shooting from ground level
- Fire shut down capability
- 45 dBA*

OPTIONS

- Mounting Extension
- Additional Powder Coating Options
- NEMA 4X VFD Enclosure
- NEMA 4X Remote Enclosure
- Corrosion Resistant Package (Consult Factory)
- iFan 4.3
- iFan 7.0
- iFan 10.0
- Multi Fan Remote (2-6)

STANDARD COLORS Custom colors and

combinations are available on frame,

mount & winglets.

- BAS Integration
- Slave Remote

STANDARD CONTROL





IFAN™ NETWORK CONTROL

8'(2.4M) 10'(3.0M) 12'(3.7M) 14'(4.3M) 16'(4.9M) 18'(5.5M) 20'(6.1M) 24'(7.3M)





iFan 4.3

iFan 43

DIAMETER SIZES



iFan 10.0



designs without notice and without incurring obligations.

Entrematic products may be the subject of one or more U.S. and/or foreign, issued and/or pending, design and/or utility patents.

1612 Hutton Dr. Suite 140, Dallas, TX 75006 866.696.2464 www.epicfan.com



Epic and Epic Fans as words and logos are registered trad belonging to Entrematic Group AB or other companies controlled by the same organization. All rights reserved.

> ©Entrematic Group AB 2020. All rights reserved. Printed in USA. Form #ECB-SDHVI S-0120



^{*}Results of sound measurement in the field may vary due to variations in surface types, environment and conditions.